

CIRCULAR REINFORCED ELASTOMERIC BEARING PAD

TECHNICAL SPECIFICATIONS BEARING PAD TYPE R-BP CIRCULAR

Ø (mm)	N/mm ²	H(mm)	Displacement +/- (mm)	Total rubber thickness (mm)	Weight (kg)
350	12,5	24	11,4	16	8 Kg
350	12,5	39	18,9	27	12,5 Kg
350	12,5	54	26,8	38	16,7 Kg
350	12,5	69	34,5	49	21,2 Kg
350	12,5	84	42,2	60	25,4 Kg
350	12,5	99	49,7	71	29,7 Kg
350	12,5	114	53,9	82	34 Kg
350	12,5	129	58,4	93	38,4 Kg
350	12,5	144	62,8	104	42,7 Kg
400	15,0	24	11,4	16	10,7 Kg
400	15,0	39	19	27	16,3 Kg
400	15,0	54	26,8	38	21,9 Kg
400	15,0	69	34,5	49	27,5 Kg
400	15,0	84	42,2	60	33 Kg
400	15,0	99	49,7	71	38,7 Kg
400	15,0	114	57,2	82	44,4 Kg.
400	15,0	129	61,3	93	50,2 Kg
400	15,0	144	65,8	104	55,6 Kg
400	15,0	159	70,2	115	61,3 Kg
500	15,0	24	11,4	16	16,5 Kg
500	15,0	39	19	27	25,3 Kg
500	15,0	54	26,8	38	34 Kg
500	15,0	69	34,5	49	42,9 Kg
500	15,0	84	42,2	60	51,6 Kg
500	15,0	99	49,9	71	60,4 Kg
500	15,0	114	57,6	82	69 Kg
500	15,0	129	65,3	93	78 Kg
500	15,0	144	72,2	104	86,8 Kg
500	15,0	159	76,2	115	95,6 Kg
500	15,0	174	80,6	126	104,3 Kg
500	15,0	189	84,9	137	113,2 Kg
500	15,0	204	89,6	148	121,9 Kg

