

CIRCULAR REINFORCED ELASTOMERIC BEARING PAD

TECHNICAL SPECIFICATIONS BEARING PAD TYPE R-BP CIRCULAR

Ø (mm)	N/mm ²	H(mm)	Displacement +/- (mm)	Total rubber thickness (mm)	Weight (kg)
850	15,0	33	16,7	23	60,8 Kg
850	15,0	56	28,9	41	95,5 Kg
850	15,0	79	41,9	59	130 Kg
850	15,0	102	54	77	164,6 Kg
850	15,0	125	66,8	95	199 Kg
850	15,0	148	79,7	113	233,6 Kg
850	15,0	171	91,9	131	268 Kg
850	15,0	194	104,9	149	302,7 Kg
850	15,0	217	117	167	337 Kg
850	15,0	240	128,6	185	371,8 Kg
850	15,0	263	135,8	203	406 Kg
850	15,0	286	142,6	221	440,8 Kg
850	15,0	309	149,9	239	475,4 Kg
850	15,0	332	157	257	510,4 Kg
900	15,0	33	16,7	23	68,2 Kg
900	15,0	56	29	41	106,9 Kg
900	15,0	79	41,9	59	145,8 Kg
900	15,0	102	54,2	77	184,8 Kg
900	15,0	125	66,8	95	223,2 Kg
900	15,0	148	79,7	113	261,9 Kg
900	15,0	171	92	131	300,6 Kg
900	15,0	194	104,9	149	339,3 Kg
900	15,0	217	117,2	167	378 Kg
900	15,0	240	128,6	185	416,7 Kg
900	15,0	263	135,8	203	455,5 Kg
900	15,0	286	142,8	221	494,2 Kg
900	15,0	309	149,9	239	532,9 Kg
900	15,0	332	157	257	571,6 Kg

