



REINFORCED ELASTOMERIC BEARING PAD

TECHNICAL SPECIFICATIONS BEARING PAD TYPE R-BP RECTANGULAR

| Dimensions (mm) | mm2 | H(mm) | Displacement +/- (mm) | Total rubber thickness (mm) | Weight (kg) |
|-----------------|-----|-------|-----------------------|-----------------------------|-------------|
| 200×400 | 2,5 | 19 | 9,3 | 13 | 5,3 Kg |
| 200×400 | 2,5 | 30 | 14,9 | 21 | 7,10Kg |
| 200×400 | 2,5 | 41 | 20,5 | 29 | 10,7Kg |
| 200×400 | 2,5 | 52 | 26 | 37 | 13,3 Kg |
| 200×400 | 2,5 | 63 | 30,2 | 45 | 15,9 Kg |
| 200×400 | 2,5 | 74 | 33,4 | 53 | 18,7 Kg |
| 200×400 | 2,5 | 85 | 36,2 | 61 | 21,3 Kg |
| 250×400 | 2,5 | 19 | 9,3 | 13 | 6,6 Kg |
| 250×400 | 2,5 | 30 | 14,9 | 21 | 9,9 Kg |
| 250×400 | 2,5 | 41 | 20,5 | 29 | 13,3 Kg |
| 250×400 | 2,5 | 52 | 26 | 37 | 16,6 Kg |
| 250×400 | 2,5 | 63 | 31,7 | 45 | 19,9 Kg |
| 250×400 | 2,5 | 74 | 36,4 | 53 | 23 Kg |
| 250×400 | 2,5 | 85 | 39,6 | 61 | 26,6 Kg |
| 250×400 | 2,5 | 96 | 42,8 | 69 | 29,9 Kg |
| 300×400 | 5,0 | 19 | 9,3 | 13 | 7,9 Kg |
| 300×400 | 5,0 | 30 | 14,9 | 21 | 11,9 Kg |
| 300×400 | 5,0 | 41 | 20,5 | 29 | 15,9 Kg |
| 300×400 | 5,0 | 52 | 26 | 37 | 19,9 Kg |
| 300×400 | 5,0 | 63 | 31,7 | 45 | 23,8 Kg |
| 300×400 | 5,0 | 74 | 37,3 | 53 | 27,8 Kg |
| 300×400 | 5,0 | 85 | 42,7 | 61 | 31,8 Kg |
| 300×400 | 5,0 | 96 | 45,8 | 69 | 35,8 Kg |
| 300×400 | 5,0 | 107 | 49 | 77 | 39,8 Kg |
| 300×400 | 5,0 | 118 | 52,2 | 85 | 43,8 Kg |
| 350×450 | 5,0 | 24 | 11,4 | 16 | 13,3 Kg |
| 350×450 | 5,0 | 39 | 19 | 27 | 20,4 Kg |
| 350×450 | 5,0 | 54 | 26,8 | 38 | 27,4 Kg |
| 350×450 | 5,0 | 69 | 34,5 | 49 | 34,5 Kg |
| 350×450 | 5,0 | 84 | 42,2 | 60 | 41,5 Kg |
| 350×450 | 5,0 | 99 | 49,7 | 71 | 48,6 Kg |
| 350×450 | 5,0 | 114 | 54 | 82 | 55,6 Kg |
| 350×450 | 5,0 | 129 | 58,4 | 93 | 62,7 Kg |
| 350×450 | 5,0 | 144 | 62,8 | 104 | 69,7 Kg |

