



REINFORCED ELASTOMERIC BEARING PAD

TECHNICAL SPECIFICATIONS BEARING PAD TYPE R-BP RECTANGULAR

Dimensions (mm)	N/mm ²	H(mm)	Displacement +/- (mm)	Total rubber thickness (mm)	Weight (kg)
400×500	15,0	24	11,5	16	1 ,9 Kg
400×500	15,0	39	18,9	27	25,9 Kg
400×500	15,0	54	26,9	38	34,8 Kg
400×500	15,0	69	34,6	49	43,8 Kg
400×500	15,0	84	42,3	60	52,7 Kg
400×500	15,0	99	49,8	71	61,7 Kg
400×500	15,0	114	57,3	82	70,6 Kg
400×500	15,0	129	61,5	93	79,6 Kg
400×500	15,0	144	65,9	104	88,5 Kg
400×500	15,0	159	70,3	115	97,5 Kg
400×600	15,0	24	11,5	16	20 Kg
400×600	15,0	39	19	27	30,9 Kg
400×500	15,0	54	26,9	38	41,7 Kg
400×600	15,0	69	34,6	49	52,4 Kg
400×600	15,0	84	42,3	60	62 ,9 Kg
400×600	15,0	99	49,8	71	73,9 Kg
400×600	15,0	114	57,3	82	84,7 Kg
400×600	15,0	129	61,5	93	95,4 Kg
400×600	15,0	144	65,9	104	105,6 Kg
400×600	15,0	159	70,3	115	116,9 Kg
400×600	15,0	174	74,7	126	127,6 Kg
500×600	15,0	24	11,5	16	25 Kg
500×600	15,0	39	19	27	38,6 Kg
500×500	15,0	54	26,9	38	51,9 Kg
500×600	15,0	69	34,6	49	65,5 Kg
500×600	15,0	84	42,3	60	23,8 Kg
500×600	15,0	99	49,9	71	78,9 Kg
500×600	15,0	114	57,7	82	91,9 Kg
500×600	15,0	129	65,4	93	105,7Kg
500×600	15,0	144	72,3	104	119 Kg
500×600	15,0	159	76,3	115	132,6Kg
500×600	15,0	174	80,7	126	145,4Kg
500×600	15,0	189	84,9	137	172,9 Kg
500×600	15,0	204	89,5	148	185,9Kg

