



REINFORCED ELASTOMERIC BEARING PAD

TECHNICAL SPECIFICATIONS BEARING PAD TYPE R-BP RECTANGULAR

Dimensions (mm)	N/mm ²	H(mm)	Displacement +/- (mm)	Total rubber thickness (mm)	Weight (kg)
600×700	15,0	30	14,6	20	43,8 Kg
600×700	15,0	50	24,7	35	67,10 Kg
600×700	15,0	70	35,6	50	91,11 Kg
600×700	15,0	90	45,8	65	115,9 Kg
600×700	15,0	110	56,6	80	140 Kg
600×700	15,0	130	66,8	95	164 Kg
600×700	15,0	150	77,6	110	188 Kg
600×700	15,0	170	86,8	125	212,6 Kg
600×700	15,0	190	92,6	140	236,7 Kg
600×700	15,0	210	98,6	155	260,8 Kg
600×700	15,0	230	104,6	170	284,9 Kg
700×800	15,0	30	14,6	20	57,13 Kg
700×800	15,0	50	24,7	35	90 Kg
700×800	15,0	70	35,6	50	122,6 Kg
700×800	15,0	90	45,8	65	154,7 Kg
700×800	15,0	110	56,6	80	186,9 Kg
700×800	15,0	130	66,8	95	219 Kg
700×800	15,0	150	77,6	110	251 Kg
700×800	15,0	170	87,8	125	283 Kg
700×800	15,0	190	98,3	140	315 Kg
700×800	15,0	210	104,6	155	347,6 Kg
700×800	15,0	230	110,6	170	379,7 Kg
700×800	15,0	250	116,6	185	411,9 Kg
700×800	15,0	270	122,6	200	443,9 Kg
800×800	15,0	33	16,7	23	24,8 Kg
800×800	15,0	56	28,8	41	107,7 Kg
800×800	15,0	79	41,9	59	146,7 Kg
800×800	15,0	102	54	77	185,7 Kg
800×800	15,0	125	66,8	95	224,6 Kg
800×800	15,0	148	79,7	113	263,6 Kg
800×800	15,0	171	91,9	131	302,6 Kg
800×800	15,0	194	104,9	149	341,5 Kg
800×800	15,0	217	114,9	167	381 Kg
800×800	15,0	240	122,6	185	419 Kg
800×800	15,0	263	129,8	203	458 Kg
800×800	15,0	286	136,6	221	497 Kg
800×800	15,0	309	143,5	239	536 Kg

